



# Two-axle fuelling platform without fuelling equipment

Thanks to its gentle ascent, the two-axle fuelling platform makes it possible to carry out refuelling from any tread.

## Product description

- Platform height: 1.60 metres
- This product can be ordered with towing eye or ball coupling on its tow bar depending on the towing vehicle used.
- This product allows personnel to work at heights from approx. 2.90 to 3.50 m.
- A platform (450 x 650 mm) optimised for secure footing offers enough space for refuelling to be performed ergonomically.
- The treads and platform are fitted with R13 anti-slip safety panels that allow water to drain easily, offering an extremely high level of safety.
- The 415 mm pneumatic tyres in combination with a tow bar allow for towing speeds of up to 30 km/h.
- Our platforms comply with the European standards EN 12312-5 and EN 1915-1.



## Hints and special features

No fuelling equipment is included for this product variant. However, the same product is also available with fuelling equipment, either already or not yet primed.



Standards used: DIN EN 1915 - General requirements  
Part 1 - Basic safety requirements  
Part 2 - Stability and strength requirements  
DIN EN 12312 - Aircraft ground support equipment  
Part 5 - Aircraft fuelling equipment  
Part 8 - Maintenance stairs and platforms

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 25/6/2026  
Subject to change or error.