



Two-axle fuelling platform without fuelling equipment

Thanks to its gentle ascent, the two-axle fuelling platform makes it possible to carry out refuelling from any tread.

Product description

- Platform height: 1.60 metres
- This product can be ordered with towing eye or ball coupling on its tow bar depending on the towing vehicle used.
- This product allows personnel to work at heights from approx. 2.90 to 3.50 m.
- A platform (450 x 650 mm) optimised for secure footing offers enough space for refuelling to be performed ergonomically.
- The treads and platform are fitted with R13 anti-slip safety panels that allow water to drain easily, offering an extremely high level of safety.
- The 415 mm pneumatic tyres in combination with a tow bar allow for towing speeds of up to 30 km/h.
- Our platforms comply with the European standards EN 12312-5 and EN 1915-1.



Hints and special features

No fuelling equipment is included for this product variant. However, the same product is also available



ZARGES

More information about the product, accessories and spare parts:
<https://www.zarges.com/uk/products/two-axle-fuelling-platform-without-fuelling-equipment>



with fuelling equipment, either already or not yet primed.

Standards used:
DIN EN 1915 - General requirements
Part 1 - Basic safety requirements
Part 2 - Stability and strength requirements
DIN EN 12312 - Aircraft ground support equipment
Part 5 - Aircraft fuelling equipment
Part 8 - Maintenance stairs and platforms