



GRP Swingback Step

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism Rigid locking bar	Connection between stiles and rungs/stiles riveted	Load capacity max. 150 kg	Material Aluminium / plastic	Standards EN 131 professional
Stile depth 80 mm	Stile depth 48 mm	Stile depth steps/back stay 80mm / 48mm	Storage tray Plastic	Tread depth 80 mm



Type of rungs/treads serrated	Vertical distance between each rung/tread 298 mm	Warranty 10 years
---	--	-----------------------------

Product variants

SKU 300514	SKU 300515	SKU 300516
Base 0,85 m × 0,47 m	Base 1,04 m × 0,51 m	Base 1,22 m × 0,54 m
Number of rungs, incl. platform 4	Number of rungs, incl. platform 5	Number of rungs, incl. platform 6
Overall base width 0.47 m	Overall base width 0.51 m	Overall base width 0.54 m
Overall length 1.24 m	Overall length 1.54 m	Overall length 1.84 m
Transport dimensions approx. 1.240 mm × approx. 470 mm × approx. 160 mm	Transport dimensions approx. 1.540 mm × approx. 510 mm × approx. 160 mm	Transport dimensions approx. 1.840 mm × approx. 540 mm × approx. 160 mm
Vertical ladder height 1.12 m	Vertical ladder height 1.39 m	Vertical ladder height 1.67 m
Weight 6.69 kg	Weight 7.6 kg	Weight 8.7 kg
SKU 300518	SKU 300520	
Base 1,6 m × 0,62 m	Base 1,97 m × 0,69 m	



Number of rungs, incl. platform	Number of rungs, incl. platform
8	10
Overall base width	Overall base width
0.62 m	0.69 m
Overall length	Overall length
2.42 m	3.02 m
Transport dimensions	Transport dimensions
approx. 2.420 mm × approx. 620 mm × approx. 160 mm	approx. 3.020 mm × approx. 690 mm × approx. 160 mm
Vertical ladder height	Vertical ladder height
2.23 m	2.79 m
Weight	Weight
11.51 kg	16.46 kg