



GRP Swingback Step

Constructed from strong and resilient fibreglass, the ZARGES fibreglass Swingback Stepladder is long-lasting and capable of withstanding heavy use. Ideal for use near electrical hazards.

Product description

- Non-conductive fibreglass stiles ideal for working around electricity.
- Integral tool tray for holding tools and equipment.
- Semi-tubular rivets provide rigid fixings.
- H-spreaders offer single-handed operation and add to the strength of the ladder.
- Generous 298mm tread pitch gives excellent working heights.
- Heavy-duty slip-resistant tread profile for added strength and security.
- Heavy-duty bracing at the foot for extra support.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism	Rigid locking bar
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	Aluminium / plastic
Standards	EN 131 professional



Stile depth	80 mm
Stile depth	48 mm
Stile depth steps/back stay	80mm / 48mm
Storage tray	Plastic
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	298 mm
Warranty	10 years

Product variants

	300514	300515	300516	300518	300520
Base	0,85 m × 0,47 m	1,04 m × 0,51 m	1,22 m × 0,54 m	1,6 m × 0,62 m	1,97 m × 0,69 m
Number of rungs, incl. platform	4	5	6	8	10
Overall base width	0.47 m	0.51 m	0.54 m	0.62 m	0.69 m
Overall length	1.24 m	1.54 m	1.84 m	2.42 m	3.02 m
Transport dimensions	approx. 1.240 mm × approx. 470 mm × approx. 160 mm	approx. 1.540 mm × approx. 510 mm × approx. 160 mm	approx. 1.840 mm × approx. 540 mm × approx. 160 mm	approx. 2.420 mm × approx. 620 mm × approx. 160 mm	approx. 3.020 mm × approx. 690 mm × approx. 160 mm
Vertical ladder height	1.12 m	1.39 m	1.67 m	2.23 m	2.79 m
Weight	6.69 kg	7.6 kg	8.7 kg	11.51 kg	16.46 kg

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 13/5/2026

Subject to change or error.