



# Industrial Swingback Step

The ultimate builders step - built to meet the demands of day to day use

## Product description

- Reinforced with a patented 7-point connection system and a central steel rod that runs right through the tread.
- Two integrated bucket hooks.
- Treads 85 mm deep for safe standing.
- Smooth, grip-friendly external stile surfaces.
- Stability through slip-resistant plastic end caps.
- High stability thanks to fold-down locking bar on both sides.



## Hints and special features

Complies with EN 131 Professional.



## Product features

Anti-splay mechanism <b>Rigid locking bar</b>	Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>max. 150 kg</b>	Stile depth <b>87 mm</b>
Tread depth <b>85 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>218 mm</b>	Warranty <b>10 years</b>	


## Product variants



SKU <b>49604</b>	SKU <b>49605</b>	SKU <b>49606</b>
Base <b>0,66 m × 0,43 m</b>	Base <b>0,8 m × 0,45 m</b>	Base <b>0,95 m × 0,48 m</b>
Number of rungs, incl. platform <b>4</b>	Number of rungs, incl. platform <b>5</b>	Number of rungs, incl. platform <b>6</b>
Overall base width <b>0.43 m</b>	Overall base width <b>0.45 m</b>	Overall base width <b>0.48 m</b>
Overall length <b>0.98 m</b>	Overall length <b>1.21 m</b>	Overall length <b>1.44 m</b>
Stile depth <b>40 mm</b>	Stile depth <b>40 mm</b>	Stile depth <b>40 mm</b>
Stile depth steps/back stay <b>87mm / 40mm</b>	Stile depth steps/back stay <b>87mm / 40mm</b>	Stile depth steps/back stay <b>87mm / 40mm</b>
Transport dimensions <b>approx. 980 mm × approx. 430 mm × approx. 160 mm</b>	Transport dimensions <b>approx. 1.210 mm × approx. 450 mm × approx. 160 mm</b>	Transport dimensions <b>approx. 1.440 mm × approx. 475 mm × approx. 160 mm</b>
Vertical ladder height <b>0.87 m</b>	Vertical ladder height <b>1.08 m</b>	Vertical ladder height <b>1.3 m</b>
Working height <b>2.45 m</b>	Working height <b>2.65 m</b>	Working height <b>2.85 m</b>
SKU <b>49607</b>	SKU <b>49608</b>	SKU <b>49610</b>
Base <b>1,1 m × 0,5 m</b>	Base <b>1,24 m × 0,52 m</b>	Base <b>1,53 m × 0,57 m</b>



Number of rungs, incl. platform	Number of rungs, incl. platform	Number of rungs, incl. platform
<b>7</b>	<b>8</b>	<b>10</b>
Overall base width	Overall base width	Overall base width
<b>0.5 m</b>	<b>0.52 m</b>	<b>0.57 m</b>
Overall length	Overall length	Overall length
<b>1.67 m</b>	<b>1.89 m</b>	<b>2.36 m</b>
Stile depth	Stile depth	Stile depth
<b>40 mm</b>	<b>40 mm</b>	<b>55 mm</b>
Stile depth steps/back stay	Stile depth steps/back stay	Stile depth steps/back stay
<b>87mm / 40mm</b>	<b>87mm / 40mm</b>	<b>87mm / 55mm</b>
Transport dimensions	Transport dimensions	Transport dimensions
<b>approx. 1.670 mm × approx. 505 mm × approx. 160 mm</b>	<b>approx. 1.895 mm × approx. 525 mm × approx. 160 mm</b>	<b>approx. 2.360 mm × approx. 575 mm × approx. 160 mm</b>
Vertical ladder height	Vertical ladder height	Vertical ladder height
<b>1.51 m</b>	<b>1.73 m</b>	<b>2.16 m</b>
Working height	Working height	Working height
<b>3.1 m</b>	<b>3.25 m</b>	<b>3.75 m</b>
SKU		
<b>49612</b>		
Base		
<b>1,82 m × 0,62 m</b>		
Number of rungs, incl. platform		
<b>12</b>		
Overall base width		
<b>0.62 m</b>		



Overall length

**2.82 m**

Stile depth

**55 mm**

Stile depth steps/back stay

**87mm / 55mm**

Transport dimensions

**approx. 2.820 mm × approx. 620  
mm × approx. 160 mm**

Vertical ladder height

**2.6 m**

Working height

**4.25 m**