

# Trade swingback step

Economy range of Class 1 swingback steps.

## Product description

- Treads 85 mm deep for safe standing.
- Rigid locking bar on both sides.
- Non-slip plastic end caps.

## Hints and special features

Complies with EN 131 Professional.




## Product features

|  |   |  |                                     |                             |
|--|---|--|-------------------------------------|-----------------------------|
| Anti-splay mechanism<br><b>Rigid locking bar</b> | Coating<br><b>natural</b>               | Connection between stiles and rungs/stiles<br><b>riveted</b> | Load capacity<br><b>max. 150 kg</b> | Stile depth<br><b>82 mm</b> |
| Tread depth<br><b>85 mm</b>                      | Type of rungs/treads<br><b>serrated</b> | Warranty<br><b>10 years</b>                                  |                                     |                             |

## Product variants

|  |  |
|--|--|
| SKU<br><b>100510</b>                         | SKU<br><b>100512</b>                         |
| Base<br><b>1,62 m × 0,59 m</b>               | Base<br><b>1,92 m × 0,64 m</b>               |
| Number of rungs, incl. platform<br><b>10</b> | Number of rungs, incl. platform<br><b>12</b> |
| Overall base width                           | Overall base width                           |



| <b>0.59 m</b>               | <b>0.64 m</b>               |
|-----------------------------|-----------------------------|
| Overall length              | Overall length              |
| <b>2.37 m</b>               | <b>2.83 m</b>               |
| Stile depth                 | Stile depth                 |
| <b>40 mm</b>                | <b>50 mm</b>                |
| Stile depth steps/back stay | Stile depth steps/back stay |
| <b>82mm / 40mm</b>          | <b>82mm / 50mm</b>          |
| Vertical ladder height      | Vertical ladder height      |
| <b>2.11 m</b>               | <b>2.53 m</b>               |