



# Skymaster EFAmix X

The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.

## Product description

- The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fire-reinforced plastic.
- One rigid locking bar.
- Aluminium rungs (30 x 30 mm).
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Locks safely by means of rung hooks and locking tab.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.

## Product features



Certification	TÜV-SÜD
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	5.8 m
Length as 2-part single ladder and as stepladder with push-on section	4.1 m
Load capacity	max. 150 kg
Material	Aluminium / plastic
Number of rungs	8
Number of rungs	3 × 8
Overall length, retracted	2.45 m
Standards	EN 131 professional
Stile depth	73 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Wide crosspiece	1 m
Working height as 3-part single ladder	6.55 m

**ZARGES (U.K.) Ltd.**

8 Holdom Avenue, Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 12/5/2026  
 Subject to change or error.