



# Skymaster EFAmix X

The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.

## Product description

- The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fire-reinforced plastic.
- One rigid locking bar.
- Aluminium rungs (30 x 30 mm).
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Locks safely by means of rung hooks and locking tab.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.

## Product features



Connection between stiles and rungs/stiles <b>flanged</b>	Ladder length as 3-part single ladder <b>5.8 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>4.1 m</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium / plastic</b>
Number of rungs <b>8</b>	Number of rungs <b>3 × 8</b>	Overall length, retracted <b>2.45 m</b>	Standards <b>EN 131 professional</b>	Stile depth <b>73 mm</b>
Tread depth <b>30 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>265 mm</b>	Warranty <b>10 years</b>	Wide crosspiece <b>1 m</b>
Working height as 3-part single ladder <b>6.55 m</b>				

## Product variants