



Combination ladder, 3 sections

Our base model: lightweight and yet robust.

Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength Perlon straps prevent splay.



Hints and special features

Complies with EN 131 Professional.




Product features

Coating natural	Connection between stiles and rungs/stiles flanged	Load capacity max. 150 kg	Material aluminium	Standards EN 131 professional
Tread depth 24 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm	Warranty 10 years	

Product variants

SKU 48980	SKU 48981	SKU 48982
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	Ladder length as 3-part single ladder



4 m	5.12 m	5.96 m
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section
2.53 m	3.37 m	3.93 m
Number of rungs	Number of rungs	Number of rungs
3 × 7	3 × 8	3 × 9
Overall length, retracted	Overall length, retracted	Overall length, retracted
2.04 m	2.32 m	2.6 m
Transport dimensions	Transport dimensions	Transport dimensions
approx. 2.038 mm × approx. 460 mm × approx. 135 mm	approx. 2.318 mm × approx. 460 mm × approx. 180 mm	approx. 2.598 mm × approx. 460 mm × approx. 190 mm
Weight	Weight	Weight
9.9 kg	13.3 kg	14.9 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
0.74 m	0.88 m	0.99 m
Working height as 3-part single ladder	Working height as 3-part single ladder	Working height as 3-part single ladder
max. approx. 4.8 m	max. approx. 5.9 m	max. approx. 6.7 m
SKU	SKU	
48983	48984	
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	
6.52 m	6.8 m	
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	
4.49 m	4.77 m	
Number of rungs	Number of rungs	
3 × 10	3 × 11	



Overall length, retracted 2.88 m	Overall length, retracted 3.16 m
Transport dimensions approx. 2.878 mm × approx. 460 mm × approx. 200 mm	Transport dimensions approx. 3.158 mm × approx. 460 mm × approx. 220 mm
Weight 16.9 kg	Weight 20.1 kg
Wide crosspiece 0.99 m	Wide crosspiece 1.2 m
Working height as 3-part single ladder max. approx. 7.2 m	Working height as 3-part single ladder max. approx. 7.5 m