



# Combination ladder, 3 sections

Our base model: lightweight and yet robust.

## Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength Perlon straps prevent splay.



## Hints and special features

Complies with EN 131 Professional.



## Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>	Standards <b>EN 131 professional</b>
Tread depth <b>24 mm</b>	Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>265 mm</b>	Warranty <b>10 years</b>	

## Product variants

SKU <b>48980</b>	SKU <b>48981</b>	SKU <b>48982</b>
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	Ladder length as 3-part single ladder



<b>4 m</b>	<b>5.12 m</b>	<b>5.96 m</b>
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section
<b>2.53 m</b>	<b>3.37 m</b>	<b>3.93 m</b>
Number of rungs	Number of rungs	Number of rungs
<b>3 × 7</b>	<b>3 × 8</b>	<b>3 × 9</b>
Overall length, retracted	Overall length, retracted	Overall length, retracted
<b>2.04 m</b>	<b>2.32 m</b>	<b>2.6 m</b>
Transport dimensions	Transport dimensions	Transport dimensions
<b>approx. 2.038 mm × approx. 460 mm × approx. 135 mm</b>	<b>approx. 2.318 mm × approx. 460 mm × approx. 180 mm</b>	<b>approx. 2.598 mm × approx. 460 mm × approx. 190 mm</b>
Weight	Weight	Weight
<b>9.9 kg</b>	<b>13.3 kg</b>	<b>14.9 kg</b>
Wide crosspiece	Wide crosspiece	Wide crosspiece
<b>0.74 m</b>	<b>0.88 m</b>	<b>0.99 m</b>
Working height as 3-part single ladder	Working height as 3-part single ladder	Working height as 3-part single ladder
<b>max. approx. 4.8 m</b>	<b>max. approx. 5.9 m</b>	<b>max. approx. 6.7 m</b>
SKU	SKU	
<b>48983</b>	<b>48984</b>	
Ladder length as 3-part single ladder	Ladder length as 3-part single ladder	
<b>6.52 m</b>	<b>6.8 m</b>	
Length as 2-part single ladder and as stepladder with push-on section	Length as 2-part single ladder and as stepladder with push-on section	
<b>4.49 m</b>	<b>4.77 m</b>	
Number of rungs	Number of rungs	
<b>3 × 10</b>	<b>3 × 11</b>	



Overall length, retracted <b>2.88 m</b>	Overall length, retracted <b>3.16 m</b>
Transport dimensions <b>approx. 2.878 mm × approx. 460 mm × approx. 200 mm</b>	Transport dimensions <b>approx. 3.158 mm × approx. 460 mm × approx. 220 mm</b>
Weight <b>16.9 kg</b>	Weight <b>20.1 kg</b>
Wide crosspiece <b>0.99 m</b>	Wide crosspiece <b>1.2 m</b>
Working height as 3-part single ladder <b>max. approx. 7.2 m</b>	Working height as 3-part single ladder <b>max. approx. 7.5 m</b>