DATA SHEET

Combination ladder, 3 sections

Our base model: lightweight and yet robust.





PRODUCT DESCRIPTION

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Coating	natural
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	aluminium
Standards	EN 131 professional

Property	Value
Tread depth	24 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years

PRODUCT VARIANTS

	48980	48981	48982	48983	48984
Ladder length as 3-part single ladder	4 m	5.12 m	5.96 m	6.52 m	6.8 m
Length as 2-part single ladder and as stepladder with push-on section	2.53 m	3.37 m	3.93 m	4.49 m	4.77 m
Number of rungs	3 × 7	3 × 8	3 × 9	3 × 10	3 × 11
Overall length, retracted	2.04 m	2.32 m	2.6 m	2.88 m	3.16 m
Transport dimensions	approx. 2.038 mm × approx. 460 mm × approx. 135 mm	approx. 2.318 mm × approx. 460 mm × approx. 180 mm	approx. 2.598 mm × approx. 460 mm × approx. 190 mm	approx. 2.878 mm × approx. 460 mm × approx. 200 mm	approx. 3.158 mm × approx. 460 mm × approx. 220 mm
Weight	9.9 kg	13.3 kg	14.9 kg	16.9 kg	20.1 kg
Wide crosspiece	0.74 m	0.88 m	0.99 m	0.99 m	1.2 m
Working height as 3-part single ladder	max. approx. 4.8 m	max. approx. 5.9 m	max. approx. 6.7 m	max. approx. 7.2 m	max. approx. 7.5 m

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 8/11/2026
Subject to change or error.