



XLstep P


Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Abrasion-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183



Product features

| | | | | |
|------------------------------------|---|--------------------------------|---------------------------------------|-----------------------------------|
| Coating anodised | Connection Stile-Rung riveted | Load capacity 150 kg | Material Anodised aluminium | Pitch rung/tread 250 mm |
| Platform length 300 mm | Platform width 400 mm | Standards EN 14183 | Stile depth 48 mm | Tread depth 92 mm |
| Type rung/tread serrated | Warranty 10 years | | | |

Product variants



| SKU 40101 | SKU 40102 | SKU 40103 |
|---|---|---|
| Base 0,64 m × 0,6 m | Base 0,82 m × 0,68 m | Base 0,99 m × 0,76 m |
| Number of treads 2 × 2 | Number of treads 2 × 3 | Number of treads 2 × 4 |
| Overall base width 0.6 m | Overall base width 0.68 m | Overall base width 0.76 m |
| Platform height 0.49 m | Platform height 0.74 m | Platform height 0.99 m |
| Transport dimensions approx. 580 mm × approx. 600 mm × approx. 290 mm | Transport dimensions approx. 840 mm × approx. 680 mm × approx. 290 mm | Transport dimensions approx. 1.105 mm × approx. 760 mm × approx. 290 mm |
| Weight 4.7 kg | Weight 6.1 kg | Weight 7.8 kg |
| Working height 2.49 m | Working height 2.74 m | Working height 2.99 m |