



# XLstep P

## Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimum stability thanks to rigid locking bar on both sides.
- Double-sided access.
- Wear-resistant, anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



## Hints and special features

Complies with EN 14 183



## Product features

Coating <b>anodised</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>150 kg</b>	Material <b>Anodised aluminium</b>	Platform length <b>300 mm</b>
Platform width <b>400 mm</b>	Standards <b>EN 14183</b>	Stile depth <b>48 mm</b>	Tread depth <b>92 mm</b>	Type of rungs/treads <b>serrated</b>
Vertical distance between each rung/tread <b>250 mm</b>	Warranty <b>10 years</b>	certification-mark-pf <b>TÜV-SÜD</b>		



## Product variants

SKU <b>40101</b>	SKU <b>40102</b>	SKU <b>40103</b>
Base <b>0,64 m × 0,6 m</b>	Base <b>0,82 m × 0,68 m</b>	Base <b>0,99 m × 0,76 m</b>
Number of treads <b>2 × 2</b>	Number of treads <b>2 × 3</b>	Number of treads <b>2 × 4</b>
Overall base width <b>0.6 m</b>	Overall base width <b>0.68 m</b>	Overall base width <b>0.76 m</b>
Platform height <b>0.49 m</b>	Platform height <b>0.74 m</b>	Platform height <b>0.99 m</b>
Transport dimensions <b>approx. 580 mm × approx. 600 mm × approx. 290 mm</b>	Transport dimensions <b>approx. 840 mm × approx. 680 mm × approx. 290 mm</b>	Transport dimensions <b>approx. 1.105 mm × approx. 760 mm × approx. 290 mm</b>
Weight <b>4.7 kg</b>	Weight <b>6.1 kg</b>	Weight <b>7.8 kg</b>
Working height <b>2.49 m</b>	Working height <b>2.74 m</b>	Working height <b>2.99 m</b>