



# XLstep P

## Product description

- Handy and robust work platform in a new design.
- Platform size approx. 400 x 300 mm.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



## Hints and special features

Complies with EN 14 183



## Product features

Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium
Platform length	300 mm
Platform width	400 mm
Standards	EN 14183



Stile depth	48 mm
Tread depth	92 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Warranty	10 years

## Product variants

	40101	40102	40103
Base	0,64 m × 0,6 m	0,82 m × 0,68 m	0,99 m × 0,76 m
Number of treads	2 × 2	2 × 3	2 × 4
Overall base width	0.6 m	0.68 m	0.76 m
Platform height	0.49 m	0.74 m	0.99 m
Transport dimensions	approx. 580 mm × approx. 600 mm × approx. 290 mm	approx. 840 mm × approx. 680 mm × approx. 290 mm	approx. 1.105 m × approx. 760 mm × approx. 290 mm
Weight	4.7 kg	6.1 kg	7.8 kg
Working height	2.49 m	2.74 m	2.99 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 31/5/2026  
 Subject to change or error.