DATA SHEET

RCstep BP

PRODUCT DESCRIPTION

- Treads and platform with a unique texture for maximum slip resistance (R13).
- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.





HINTS AND SPECIAL FEATURES

Complies with EN 14183, VNA 205/2009, and AFS 2023:9.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium

Property	Value
Platform length	300 mm
Platform width	600 mm
Stile depth	48 mm
Tread depth	92 mm
Type of rungs/treads	RC tread
Vertical distance between each rung/tread	250 mm
Warranty	10 years

PRODUCT VARIANTS

	40137	40138	40139
Base	0,64 m × 0,8 m	0,82 m × 0,88 m	0,99 m × 0,96 m
Number of treads	2 × 2	2 × 3	2 × 4
Overall base width	0.8 m	0.88 m	0.96 m
Platform height	0.49 m	0.74 m	0.99 m
Standards	EN 14183,AFS 2023:9,VNA205/2009	EN 14183,AFS 2023:9,VNA205/2009	EN 14183,AFS 2023:9,VNA205/2009
Transport dimensions	approx. 580 mm × approx. 800 mm × approx. 290 mm	approx. 840 mm × approx. 880 mm × approx. 290 mm	approx. 1.105 mm × approx. 960 mm × approx. 290 mm
Weight	5.6 kg	7.4 kg	9.3 kg
Working height	2.49 m	2.74 m	2.99 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 3



Push-on end cap
SKU 21012290



Spreader without lock, left
SKU 800475



Spreader without lock, right
SKU 800476

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 15/11/2026
Subject to change or error.