



RCstep BP

Product description

- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183

Product features

Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium
Platform length	300 mm
Platform width	600 mm
Standards	EN 14183
Stile depth	48 mm
Tread depth	92 mm



Type of rungs/treads RC tread

Vertical distance between each rung/tread 250 mm

Warranty 10 years

Product variants

	40137	40138	40139
Base	0,64 m × 0,8 m	0,82 m × 0,88 m	0,99 m × 0,96 m
Number of treads	2 × 2	2 × 3	2 × 4
Overall base width	0.8 m	0.88 m	0.96 m
Platform height	0.49 m	0.74 m	0.99 m
Transport dimensions	approx. 580 mm × approx. 800 mm × approx. 290 mm	approx. 840 mm × approx. 880 mm × approx. 290 mm	approx. 1.105 mm × approx. 960 mm × approx. 290 mm
Weight	5.6 kg	7.4 kg	9.3 kg
Working height	2.49 m	2.74 m	2.99 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway

CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 2/7/2026

Subject to change or error.