DATA SHEET

RCstep SP

PRODUCT DESCRIPTION



- Treads and platform with a unique texture for maximum slip resistance (R13).
- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Single-sided access.
- The specially shaped stiles enable full use of the entire platform area.
- Extra-wide safety bar with a practical storage tray.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.

HINTS AND SPECIAL FEATURES

Complies with EN 14183, VNA 205/2009, and AFS 2023:9.

PRODUCT FEATURES

Property	Value
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium

Property	Value
Platform length	300 mm
Platform width	600 mm
Stile depth	48 mm
Storage tray	aluminium
Tread depth	92 mm
Type of rungs/treads	RC tread
Vertical distance between each rung/tread	250 mm
Warranty	10 years

PRODUCT VARIANTS

	40278	40279
Base	0,82 m × 0,88 m	1 m × 0,96 m
Number of rungs, incl. platform	3	4
Overall base width	0.88 m	0.96 m
Platform height	0.74 m	0.99 m
Standards	EN 14183,AFS 2023:9,VNA205/2009	EN 14183,AFS 2023:9,VNA205/2009
Transport dimensions	approx. 1.550 mm × approx. 880 mm × approx. 290 mm	approx. 1.810 mm × approx. 960 mm × approx. 290 mm
Weight	8.4 kg	9.6 kg
Working height	2.74 m	2.99 m

ACCESSORIES AND SPARE PARTS

SPARE PARTS 3



Push-on end cap
SKU 21012290



Spreader without lock, left
SKU 800475



Spreader without lock, right
SKU 800476

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 15/11/2026
Subject to change or error.