



# RCstep SP

## Product description

- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Single-sided access.
- Safety bar with a practical storage tray.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



## Hints and special features

Complies with EN 14 183

## Product features

Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium
Platform length	300 mm
Platform width	600 mm
Standards	EN 14183
Stile depth	48 mm



Storage tray	aluminium
Tread depth	92 mm
Type of rungs/treads	RC tread
Vertical distance between each rung/tread	250 mm
Warranty	10 years

## Product variants

	40278	40279
Base	0,82 m × 0,88 m	1 m × 0,96 m
Number of rungs, incl. platform	3	4
Overall base width	0.88 m	0.96 m
Platform height	0.74 m	0.99 m
Transport dimensions	approx. 1.550 mm × approx. 880 mm × approx. 290 mm	approx. 1.810 mm × approx. 960 mm × approx. 290 mm
Weight	8.4 kg	9.6 kg
Working height	2.74 m	2.99 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 2/7/2026  
 Subject to change or error.